

Under-Counter Glass and Dish washer UD-1

台下式洗杯/碗机 UD-1

特点及优势:

- 一键式按键操作，更方便；
- 自排水功能，更具人性化；
- 双层箱体，保温安全降噪；
- 深拉成型水箱，圆角设计，便于清洗；
- 排水泵更易排水；
- 高效三重过滤系统，清洗效果更佳



Characteristics and Advantages

- More convenient with one-key operation
- User-friendly design of automatic drain system
- Heat preservation and noise reduction by double-skin cabinet
- Easy to clean thanks to deep drawn tank
- Drain pump included for easy drain
- Triple filtering system: large tank filter with double-layer strainer keeps wash water clean for a longer time

| 可选配置 Available Configuration | | | |
|------------------------------|---|--------------|--------------|
| 电源要求 | Power Requirements | 220V/50Hz/1N | 380V/50Hz/3N |
| 进水温度 | Incoming water temperature (°C) | 10-60 | 10-60 |
| 水槽加热功率 | Tank heater (kW) | 2 | 2 |
| 漂洗加热功率 | Booster heater (kW) | 3 | 4.5 |
| 清洗水泵功率 | Wash pump (kW) | 0.55 | 0.55 |
| 总功率 | Total connected load (kW) | 3.55 | 5.05 |
| 总电流 | Total amps required (A) | 17 | 9 |
| 电源线截面 | Cross section of cable (mm ²) | 4 | 2.5 |
| 空气开关额定电流 | Rated current of circuit breaker (A) | 25 | 16 |







| 选装件 Optional Accessories | |
|--------------------------|---------------------|
| 洗涤剂分配器 | Detergent dispenser |
| 快干剂分配器 | Rinse aid dispenser |

安装接驳要求 Installation and Connection Requirements

- 电力安装需要220V/50Hz/1N或380V/50Hz/3N，外部需加装独立的空气开关
- 机器可直接与一般供水系统连接，最低水压须达到2Kg/cm²
- Connection requirements: 220V/1N + Neutral + Ground or 380V/3N + Neutral + Ground with a separate external circuit breaker
- The machine can be directly connected to water supply system. The lowest incoming water pressure should be 2Kg/cm²

技术参数 Technical Data

| 名称/型号 | Name/Model | UD-1 |
|--------|---|---------------|
| 加热方式 | Heating | Electricity |
| 外形尺寸 | External dimension (mm) | 600x600x820 |
| 最大洗涤高度 | Clearance height (mm) | 310 |
| 最大洗涤量 | Max capacity (rack/hour) | 40 |
| 最大耗水量 | Water consumption (liter/rack) | 2.4 |
| 水箱容积 | Wash tank capacity (l) | 13 |
| 升温器容积 | Booster capacity (l) | 5.5 |
| 洗涤温度 | Wash temperature (°C) | 55 - 65 |
| 漂洗温度 | Rinse temperature (°C) | 65 - 88 |
| 洗涤周期 | Wash cycle (s) | 90/110/130 |
| 进水管径 | Diameter of water inlet hose (in) | ¾ |
| 排水管径 | Diameter of drain pipe (in) | 1¼ |
| 进水压力 | Incoming water pressure (Kg/cm ²) | 2 - 5 |
| 进水硬度 | Incoming water hardness (g/l) | 0.034 - 0.103 |



- ① 分配器连接 Dispenser Connection
- ② 进水管连接 Water Inlet Connection
- ③ 排水管连接 Drain Outlet Connection
- ④ 电源连接 Cable Connection

主要使用场所 Ideal for:

- 小型餐厅、咖啡厅、酒吧等场所；
- Small restaurants, coffee shops, bars and other catering industries